

DECORFILM

WATER-BASED PROTECTIVE COATING FOR DECORATIVE FINISHES AND PAINTS

code 3740238/230

DESCRIPTION

DECORFILM is a water-based protective coating specific for protecting interior and exterior surfaces treated with decorative finishes, water-based paints and varnishes.

The urethane modified acrylic formulation creates an easy cleaning protective coat that has excellent mechanical resistance.

On walls covered with coloured water-based paints, the application of DECORFILM lessens the surface streaking phenomena.

Fast drying and non-yellowing, DECORFILM has excellent flow and adhesion properties.

INSTRUCTIONS FOR USE

Can be applied to:

- Organic decorative finishes
- Mineral decorative finishes for interior only
- Water-based paints and varnishes of various aesthetic effects
- Old paints and organic, mineral, dry, compact, absorbent and cohesive coatings.
- Determine the DECORFILM finish that is best suited for the type of product to protect. DECORFILM OPACO (code 3740238) is normally recommended for flat-satin surfaces, while DECORFILM LUCIDO (code 3740230) is generally used for glossy surfaces.
- The spreading of the glossy version over matt surfaces will alter the final appearance.
- DECORFILM has good resistance to normal household detergents. It is recommended that a preliminary cleaning test be performed on a small hidden area of the substrate in order to specifically test the resistance.
- Avoid using denatured ethyl alcohol in both pure form and in detergent solutions.
- Do not use abrasive sponges to clean the surfaces.

TECHNICAL SPECIFICATIONS

- Binder: polyurethane modified acrylic resin in aqueous dispersion.
- Specific gravity per UNI EN ISO 2811-1: 1.00 ± 0.05 kg/l
- Viscosity per UNI 8902: 1000 ± 200 cps at 25 °C
- Gloss per UNI EN ISO 2813:
3740230 gloss finish: >80 , at 60°
3740238 satin finish: $10^{\circ} \pm 2^{\circ}$, at 85°
- Drying times (at 25 C and 65% R.H.): dust free in 1 hour; to touch in 2-3 hours; to recoat after 4 hours.

PREPARING THE SURFACE

Wall surfaces:

Apply DECORFILM onto surfaces covered with decorative effects, paints or varnishes that are compact, dry and void of inconsistencies.

APPLICATION INSTRUCTIONS

- Ambient and support surface conditions:
Ambient temperature: Min. +8 °C / Max. +35 °C
Relative environmental humidity: <75%

Support surface temperature: Min. +5 °C / Max. +35 °C

Moisture level of the support surface: <10%

- Tools: brush, roller, spray, sponge trowel.
- Number of coats: 1 - 2.
- Diluent: water
- Dilution: varies depending on the absorption and the equipment used. Normally dilute first and second coat at 5-15%. For high absorbent surfaces, dilute the first coat at 25-30%.
- Clean the tools immediately after use with water.
- Approximate spreading rate: Strongly influenced by the nature of the product being covered. 10-12 m²/l per coat for average absorbing smooth surfaces.

TINTING

The product is available colourless in the flat version code 3740238 and glossy code 3740230.

STORAGE

Maximum storage temperature: +30°C

Minimum storage temperature: +5°C

The product should be preferably used within 2 years from date of manufacture when stored in original unopened containers and in appropriate temperature conditions.

SAFETY RULES

Limit value EU (Dir. 2004/42/EC)

Cat. L: Decorative effect coatings (water-base): 300 g/l (2007) / 200 g/l (2010)

DECORFIL Contains max: 100 g/l VOC

The product does not require labelling in accordance with 67/548/EEC and 1999/45/EC and its subsequent changes and updates. Use the product according to current health and safety regulations; after use, do not discard the containers in the environment; allow the residue to dry thoroughly, then treat as special waste. Store out of the reach of children. Do not dispose of residues in the sewers, waterways or ground.

For more information consult the safety data sheet.

SPECIFICATION ITEM

Urethane modified acrylic resin based interior and exterior protective paint in an aqueous dispersion.

Specific for surfaces that have been previously treated with organic decorative coatings, interior mineral coatings, water-based paints and varnishes, DECORFILM is available in a matt version code 3740238 and a glossy version code 3740230, depending on the desired aesthetic result.

DECORFILM is applied in 1-2 coats, depending on the desired aesthetic finish. The amount required will depend on the absorption of the substrate.

Supplying and application of the material € per m².

COLORIFICIO SAN MARCO guarantees that the information herein

DECORFILM

WATER-BASED PROTECTIVE COATING FOR DECORATIVE FINISHES AND PAINTS

code 3740238/230

is provided to the best of its technical and scientific knowledge and based on its experience; nonetheless, the company may not be held liable for the results obtained using these products, as application conditions are beyond its control. It is recommended to always make sure that the product is suited to each specific instance. The present sheet voids and replaces any previously existing sheets. For further technical information call the technical service +39 041 4569322.